

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 2K SPEED URETHANE CLEAR - PART A  
 PRODUCT CODE: KC-210

HMIS CODES: H F R P  
 2\*4 0 X

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: KUSTOM SHOP PRODUCTS  
 ADDRESS: 6695 RASHA STREET  
 SAN DIEGO, CA 92121-2241  
 EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 (U.S) DATE PRINTED : 02/09/06  
 EMERGENCY PHONE(CHEMTREC) : (703) 527-3887 (U.S) NAME OF PREPARER : N/A  
 INFORMATION PHONE : (800) 672-4900

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR mmHG	PRESSURE @TEMP(F)	WEIGHT PERCENT
* PARACHLOROBENZOTRIFLUORIDE OSHA PEL: NE, ACGIH TLV: NE	98-56-6	5.3	68	35
* ACETONE OSHA PEL: 1000 ppm, ACGIH TLV: 750 ppm	67-64-1	185.5	68	29.9
* XYLENE OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	6.1	68	5.7
STYRENE OSHA PEL: 100 PPM, ACGIH TLV: 50 PPM	100-42-5	4.5	68	0.26

/ Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 133 - 295                      DENSITY: 8.60 lb/gl  
 VAPOR DENSITY: HEAVIER THAN AIR                      SPECIFIC GRAVITY (H2O=1): 1.03  
 COATING V.O.C.: 1.55 lb/gl                              MATERIAL V.O.C.: 0.53 lb/gl  
 COATING V.O.C.: 186 g/l                                  MATERIAL V.O.C.: 63 g/l  
 SOLUBILITY IN WATER: Insoluble                      EVAPORATION RATE: SLOWER THAN ETHER  
 APPEARANCE AND ODOR: Pale yellow liquid with mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): 1                                      METHOD USED: TOC  
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .9                      UPPER: 12.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

Use approved self-contained breathing apparatus. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep away from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat due to pressure build-up.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**

**CONDITIONS TO AVOID**

Excessive heat, sparks or open flames

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Strong oxidizing agents, isocyanates and acids.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition may yield CO and/or CO<sub>2</sub>, oxides of nitrogen amines & other aliphatic fragments.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR**

## ===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Inhalation: Excessive inhalation of vapors may cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. High concentrations may result in narcosis.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin contact may cause irritation. Symptoms of skin irritation may be reddening, swelling, scaling or blistering. Eye contact may cause tearing, reddening and swelling of the eyes.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin absorption may cause systemic effects similar to those identified under inhalation effects.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute: May cause eye, nose and skin irritation, headache, dizziness and nausea. Ingestion may result in vomiting; aspiration of liquid into the lungs may result in aspiration pneumonitis.

Chronic: Long term exposure may lead to central nervous system depression and dermatitis.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes**

**OSHA REGULATED: Yes**

This material contains styrene oxide, which is classified as a possible carcinogen for humans (2B) by IARC. This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Pre-existing eye, skin and respiratory disorders may be aggravated.

**EMERGENCY AND FIRST AID PROCEDURES**

**INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.**

**SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE. FOR SEVERAL EXPOSURES GET UNDER SAFETY SHOWER AFTER REMOVING CLOTHING, THEN GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GIVE 1 TO 2 CUPS OF MILK OR WATER TO DRINK. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. CONSULT PHYSICIAN IMMEDIATELY.**

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

**ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA OF SPILL WITH WATER.**

**WASTE DISPOSAL METHOD**

**Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue and flammable solvent vapor. Decontaminate containers prior to disposal. DO NOT HEAT OR CUT EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

**Keep away from heat, sparks and open flame. Ground containers during storage and transfer operations. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Avoid contact with skin and eyes.**

**OTHER PRECAUTIONS**

**Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.**

===== **SECTION VIII - CONTROL MEASURES**=====**RESPIRATORY PROTECTION**

**Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Below TLV limits, use a combination vapor and particulate respirator for spray application or a vapor respirator for non-spray applications.**

**VENTILATION**

**Exhaust ventilation sufficient to keep the airborne concentration of the solvents, HDI and polyisocyanate below their respective TLV's must be utilized.**

**PROTECTIVE GLOVES**

**Chemical resistant gloves. Cover as much of the skin area as possible with appropriate clothing.**

**EYE PROTECTION**

**Safety glasses, splash goggles or face shield. Contact lenses should not be worn.**

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

**Safety showers and eyewash stations should be provided.**

**WORK/HYGIENIC PRACTICES**

**Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.**

===== **SECTION IX - REGULATORY INFORMATION**=====**CALIFORNIA PROPOSITION 65**

**This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.**

**Contains: Toluene and Benzene (Trace).**

**This product contains a chemical known to the State of California to cause cancer.**

**Contains: Benzene (Trace) and Styrene Oxide.**

**TRANSPORTATION**

**Proper Shipping Name: PAINT**

**Hazard Class: 3**

**Subsidiary Risk: N.A.**

**UN Number: UN1263**

**Packing Group: II**

**Marine Pollutant: N.A.**

**===== SECTION X - DISCLAIMER =====**

**The information contained herein is based on the data available to us and is believed to be correct. However, Kustom Shop Products makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Kustom Shop Products assumes no responsibility for injury from the use of the product described herein.**