

## MATERIAL SAFETY DATA SHEET

PRODUCT NAME: OLD-SCHOOL LACQUER SPEED PRIMER  
 PRODUCT CODE: KL-611

HMIS CODES: H F R P

2\*4 2

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: KUSTOM SHOP PRODUCTS  
 ADDRESS: 6695 RASHA STREET  
 SAN DIEGO, CA 92121-2241  
 EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 (U.S) DATE PRINTED : 02/09/06  
 EMERGENCY PHONE(CHEMTREC) : (703) 527-3887 (U.S) NAME OF PREPARER : N/A  
 INFORMATION PHONE : (800) 672-4900

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR mmHG	PRESSURE @TEMP(F)	WEIGHT PERCENT
* ACETONE OSHA PEL: 1000 ppm, ACGIH TLV: 750 ppm	67-64-1	185.5	68	20.0
* PARACHLOROBENZOTRIFLUORIDE OSHA PEL: NE, ACGIH TLV: NE	98-56-6	5.3	68	17
TITANIUM DIOXIDE (as total nuisance dust) OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3	13463-67-7	NA	NA	5
* ISOPROPYL ALCOHOL, 2-PROPANOL OSHA PEL: 400 ppm, ACGIH TLV: 400 ppm	67-63-0	32	68	3
* DI(2-ETHYLHEXYL)PHTHALATE OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3	117-81-7	0	68	1.66
DIBASIC ESTER(CAS #1119-40-0,627-93-0,106-65-0 )MIXTURE OSHA PEL: N/E, ACGIH TLV: N/E			.2	68 1
SOLVENT NAPHTHA,HEAVY AROMATIC OSHA TWA: NE, ACGIH STEL: NE, SUPPLIER RECOMMENDED TWA: 100 PPM	64742-94-5	7.5	68	1
METHYL AMYL KETONE , 2-HEPTANONE ACGIH TLV: 50 ppm	110-43-0	2.14	68	1
XYLENE OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	6.1	68	0.6
PM ACETATE OSHA PEL: N/E, ACGIH TLV: N/E	108-65-6	3.7	68	0.2
CARBON BLACK	1333-86-4	NA	NA	0.14

/ Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 133 - 723 DENSITY: 10.35 lb/gl  
 VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.24  
 COATING V.O.C.: 2.06 lb/gl MATERIAL V.O.C.: 1.10 lb/gl  
 COATING V.O.C.: 247 g/l MATERIAL V.O.C.: 131 g/l  
 SOLUBILITY IN WATER: Negligible EVAPORATION RATE: SLOWER THAN ETHER  
 APPEARANCE AND ODOR: Gray liquid with mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): 1 METHOD USED: TOC  
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .3 UPPER: 12.8

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER SPECIAL  
FIREFIGHTING PROCEDURES**

Use approved self-contained breathing apparatus. Do not use direct stream of water.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

**===== SECTION V - REACTIVITY DATA =====**

**STABILITY: STABLE**

**CONDITIONS TO AVOID**

Excessive heat, sparks or open flames.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Strong oxidizing agents,alkaline materials.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition may yield carbon dioxide and/or carbon monoxide,nitrogen oxides,methane and carboxylic acids.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR****===== SECTION VI - HEALTH HAZARD DATA =====****INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Inhalation: May cause irritation to nose, throat and respiratory tract. High vapor concentrations may cause CNS depression.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin and eye contact: May cause irritation to both.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin absorption: May cause irritation.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Ingestion: May cause vomiting which can result in aspiration of liquid into lungs. Do not induce vomiting.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute: May cause eye, skin, nose and respiratory tract irritation. Early to moderate CNS depression may be evidenced by giddiness, headache, nausea and dizziness. Aspiration of liquid into the lungs can result in aspiration pneumonitis which may be evidenced by coughing and labored breathing. Chronic:

Prolonged and repeated contact with skin may cause defatting and drying of the skin which may result in dermatitis.

**CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: No**

This material contains crystalline silica, which has been classified as a known carcinogen for humans (1) by IARC and a probable carcinogen by NTP. Crystalline silica is also a known cause of silicosis, a non-cancerous lung disease caused by excessive exposure to crystalline silica. This material contains Di(2- ethylhexyl) phthalate, which is classified as a possible carcinogen for humans (2B) by IARC and NTP. This material contains a trace amount of lead, which has been classified as a probable carcinogen to humans (2B) by IARC and NTP. This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC. This

material contains carbon black, which is classified as a possible carcinogen for humans (2B) by IARC.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Pre-existing eye, skin and respiratory disorders may be aggravated.

**EMERGENCY AND FIRST AID PROCEDURES**

**INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.**

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE PICKED UP WITH NON-SPARKING TOOLS. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS. ADD WATER TO CONTAINERS. DO NOT ALLOW MATERIALS TO BECOME DRY.

**WASTE DISPOSAL METHOD**

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store away from heat, sparks and open flames. Keep containers tightly closed when not in use. Use with adequate ventilation. Electrically bond and ground the drum while emptying. Do not allow contents to become dry.

**OTHER PRECAUTIONS**

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

**===== SECTION VIII - CONTROL MEASURES =====**

**RESPIRATORY PROTECTION**

Use a NIOSH-approved respirator if exposure exceeds TLV limits.

**VENTILATION**

Use explosion-proof ventilation as required to control vapor concentrations.

**PROTECTIVE GLOVES**

Chemical resistant gloves

**EYE PROTECTION**

Chemical goggles, safety glasses

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Eye bath and safety shower

**WORK/HYGIENIC PRACTICES**

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

**===== SECTION IX - REGULATORY INFORMATION =====**

**CALIFORNIA PROPOSITION 65**

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Toluene, Benzene and Lead (Trace).

This product contains a chemical known to the State of California to cause cancer.

Contains: Benzene, Antimony Oxide (Trace), Chromium (Trace), Lead (Trace), Crystalline Silica (Trace), Carbon Black and Di(2-ethylhexyl)Phthalate.

**TRANSPORTATION**

**Proper Shipping Name: PAINT**

**Hazard Class: 3**

**Subsidiary Risk: N.A.**

**UN Number: UN1263**

**Packing Group: II**

**Marine Pollutant: N.A.**

**===== SECTION X - DISCLAIMER =====**

**The information contained herein is based on the data available to us and is believed to be correct. However, Kustom Shop Products makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Kustom Shop Products assumes no responsibility for injury from the use of the product described herein.**