

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: POLYESTER PRIMER SURFACER RED OXIDE      HMIS CODES: H F R P  
 PRODUCT CODE: KPP-109      2\*3 1

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME:      KUSTOM SHOP PRODUCTS  
 ADDRESS:      6695 RASHA STREET  
    SAN DIEGO, CA 92121-2241  
 EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 (U.S)      DATE PRINTED : 06/06/07  
 EMERGENCY PHONE(CHEMTREC) : (703) 527-3887 (U.S)      NAME OF PREPARER : N/A  
 INFORMATION PHONE : (800) 672-4900

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR mmHG	PRESSURE @TEMP(F)	WEIGHT PERCENT
~ PARACHLOROENZOTRIFLUORIDE OSHA PEL: NE, ACGIH TLV: NE	98-56-6	5.3	68	28.69
~ STYRENE OSHA PEL: 100 PPM, ACGIH TLV: 50 PPM	100-42-5	4.5	68	12.41
IRON (III) OXIDE	1309-37-1			4.1
ACETONE OSHA PEL: 1000 ppm; 2,400 mg/m3 OSHA TWA: 750 ppm; 1,800 mg/m3 OSHA STEL: 1000 ppm; 2,400 mg/m3 ACGIH TWA: 500 ppm, STEL: 750 ppm	67-64-1	185.5	68	4
*~ CO 2-ETHYLHEXANOATE OSHA PEL: 0.1 MG/M3, ACGIH TLV: 0.05 MG/M3	136-52-7	NA	NA	0.09
~ METHYL ALCOHOL ACGIH TLV: 200 ppm OSHA PEL: 200 ppm	67-56-1	96	68	0.07

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE(Deg F): 133 - 295      DENSITY: 12.13 lb/gl  
 VAPOR DENSITY: HEAVIER THAN AIR      SPECIFIC GRAVITY (H2O=1): 1.46  
 CATALYZED COATING V.O.C.:      0.25 lbs/gl, 30 gm/l  
 CATALYZED MATERIAL V.O.C.:      0.25 lbs/gl, 30 gm/l  
 SOLUBILITY IN WATER: Negligible      EVAPORATION RATE: SLOWER THAN ETHER  
 APPEARANCE AND ODOR: Red liquid with mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT(Deg F): 1      METHOD USED: TOC  
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .9      UPPER: 36

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

**SPECIAL FIREFIGHTING PROCEDURES**

Use approved self-contained breathing apparatus. Do not use direct stream of water.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

**===== SECTION V - REACTIVITY DATA =====****STABILITY: STABLE****CONDITIONS TO AVOID**

Excessive heat, sparks or open flames.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Strong oxidizing agents

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR****===== SECTION VI - HEALTH HAZARD DATA =====****INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Inhalation: May cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. High concentrations may result in narcosis.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Eye contact: May cause severe irritation, redness, tearing and blurred vision.

Skin contact: May cause moderate irritation.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Skin absorption: May cause irritation, defatting and dermatitis.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute: May cause eye, nose, respiratory tract and skin irritation, headache, drowsiness and nausea. Ingestion may result in vomiting; aspiration (breathing in) into the lungs may result in aspiration pneumonitis. Chronic: Long term exposure may lead to central nervous system depression, dermatitis and liver and kidney damage.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No**

This material contains a cobalt compound, which is classified as a possible carcinogen for humans (2B) by IARC. This material contains styrene, which is classified as a possible carcinogen for humans (2B) by IARC.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Pre-existing eye, skin and respiratory disorders may be aggravated.

**EMERGENCY AND FIRST AID PROCEDURES**

**INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. EYE & SKIN CONTACT: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.**

**===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

**PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP. SMALL SPILLS MAY BE PICKED**

**UP WITH ABSORBENT MATERIALS.**

**WASTE DISPOSAL METHOD**

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store away from high temperatures and open flames. Keep containers tightly closed. Use with adequate ventilation.

**OTHER PRECAUTIONS**

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

===== **SECTION VIII - CONTROL MEASURES** =====

**RESPIRATORY PROTECTION**

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Where vapor does not exceed TLV limits, use NIOSH/MSHA approved respirator.

**VENTILATION**

Adequate volume and pattern to keep air contaminant concentration below current applicable OSHA or ACGIH's TLV limits.

**PROTECTIVE GLOVES**

Chemical resistant gloves

**EYE PROTECTION**

Chemical goggles, safety glasses

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Eye bath and safety shower

**WORK/HYGIENIC PRACTICES**

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== **SECTION IX - REGULATORY INFORMATION** =====

**CALIFORNIA PROPOSITION 65**

None

**TRANSPORTATION**

Proper Shipping Name: PAINT

Hazard Class: 3

Subsidiary Risk: N.A.

UN Number: UN1263

Packing Group: II

Marine Pollutant: N.A.

===== **SECTION X - DISCLAIMER** =====

The information contained herein is based on the data available to us and is believed to be correct. However, Kustom Shop Products makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Kustom Shop Products assumes no responsibility for injury from the use of the product described herein.