

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: COMPLIANT CLEANING SOLVENT
PRODUCT CODE: KT-025

HMIS CODES: H F R P
2*3 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: TCP GLOBAL CORPORATION
ADDRESS : 6695 RASHA STREET
SAN DIEGO, CA 92121-2241

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 6/16/2010
INFORMATION PHONE : (858) 909-2100 NAME OF PREPARER :

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG	@TEMP(F)
ACETONE OSHA PEL: 1000 ppm; 2,400 mg/m3 OSHA TWA: 750 ppm; 1,800 mg/m3 OSHA STEL: 1000 ppm; 2,400 mg/m3 ACGIH TWA: 500 ppm, STEL: 750 ppm	67-64-1	185.5	68
~ TOLUENE OSHA PEL: 200 ppm, ACGIH TLV: 100 ppm	108-88-3	21.8	68
~ PARACHLOROBENZOTRIFLUORIDE OSHA PEL: NE, ACGIH TLV: NE	98-56-6	5.3	68
~ XYLENE (MIXED ISOMERS) OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	6.1	68

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 133 - 285 DENSITY: 6.63 lb/gal
VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 0.8
MATERIAL V.O.C.: 0.07 lb/gal MATERIAL V.O.C.: 8 g/l
SOLUBILITY IN WATER: Miscible EVAPORATION RATE: SLOWER THAN ETHER
V.O.C. COMPOSITE VAPOR PRESSURE: 1.1 mmHg @ 68 Deg F
APPEARANCE AND ODOR: Water-white liquid with mild odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT(Deg F): 1 METHOD USED: TOC
FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .9 UPPER: 12.8

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

FLAMMABLE! Use approved self-contained breathing apparatus. Water spray will reduce the intensity of flames.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Avoid heat, sparks and open flame

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause CNS depression.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: May cause irritation to both.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: May cause CNS depression.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause irritation to nose, eyes and skin. May also cause CNS (central nervous system) depression which may be evidenced by giddiness, headache, dizziness and nausea; in extreme cases, unconsciousness and death may occur. Chronic: Prolonged or repeated contact may result in dermatitis and damage to central nervous system, liver and kidneys.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE

LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE PUMPED TO SALVAGE VESSELS. SMALL SPILLS MAY BE PICKED UP WITH AN ABSORBENT MATERIAL.

WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks and open flames. Keep containers closed when not in use. Use with adequate ventilation.

OTHER PRECAUTIONS

Do not take internally. Ground equipment to prevent accumulation of static charge. Do not cut, weld, drill or grind on or near containers.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Where vapor does not exceed TLV limits, use NIOSH/MSHA approved respirator.

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Safety glasses, splash goggles or face shield. Contact lenses should not be worn.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Safety showers and eyewash stations should be provided.

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - TRANSPORT INFORMATION =====

DOT (GROUND)

1.3 gallons (5 liters) or less:

UN1263, Paint Related Materials, 3, PGII, "Ltd. Qty."

Greater than 1.3 gallons (5 liters):

UN1263, Paint Related Materials, 3, PGII

AIR
UN1263, Paint Related Materials, 3, PGII

===== SECTION X - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Toluene -

This product contains a chemical known to the State of California to cause cancer.

Contains: Ethylbenzene -

===== SECTION XI - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, TCP GLOBAL CORPORATION makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. TCP GLOBAL CORPORATION assumes no responsibility for injury from the use of the product described herein.