

OMXgt™

HVLP GRAVITY FEED



OMXgt HVLP Gravity Feed

Order No. Model No.	*Fluid Tip Setting (mm)	Inlet Air Pressure	Applications
570008 OMX-610	1.4	20-25 psi	Base coats High solids, clear coats, and single stages Waterbornes
		25-30 psi	
		25-30 psi	
	1.6	20-25 psi	Base coats Low solids clear coats and single stages
		25-30 psi	

*Adjustable fluid control valve—.8mm to 1.8mm

DEVILBISS®

- **Superior performance** – #100 gold air cap provides excellent atomization of low V.O.C. compliant materials with less overspray and less orange peel. Excellent with high solids clearcoats
- **Complies with environmental regulations requiring HVLP**
- **Eliminates need for multiple tips and needles**– Fluid control valve adjusts from .8 mm to 1.8 mm
- **The ultimate in painter comfort** –
Lightweight (only 19 oz.) and well-balanced
Top trigger for easy spraying of horizontal surfaces without bending wrist
Light trigger pull – 2 lbs. vs. competitors' 5-6 lbs.
- **Waterborne-compatible**
- **Easy cleanup and identification of spray gun** –
Disposable black grips on gun; also available in red
Conveniently identifies base coat or clear coat gun
- **Quick cleanup and upside-down spraying** –
(with no cup lid leaks) with E-Z Liner™ disposable cup liners
- **Less time spent on refills** –
28-oz. lightweight cup
- **Includes:**
Air inlet mini-gauge (192012 / OMX-148)
Air adjusting valve (HAV-500)
28-oz. Delrin cup (190977 / OMX-467)
Red grips (192056 / OMX-490)
Gun holder (190967 / OMX-114)
(9) E-Z Liner™ disposable cup liners (190966 / OMX-70-K48)
Fluid tube cleaning brush (190976 / OMX-465)
- **Specifications:**
30 psi air inlet pressure delivers
10 psi air cap pressure at
16 cfm air volume required
192059 (OMX-5033-100) Air Cap Test Kit